

Cemex Truck Wash

Version number: GHS 1.0

Date of compilation: 2024-03-14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **Cemex Truck Wash**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Concrete and / or mortar admixtures

Uses advised against Do not use for squirting or spraying. Do not use for products which come into direct contact with the skin.

1.3 Details of the supplier of the safety data sheet

CEMEX Admixtures UK
Lawford Road, Rugby
Warwickshire CV212RY
United KingdomWebsite: www.cemex.co.uk/admixturese-mail (competent person) Dennis.Tewes@cemex.com (Dennis Tewes)

1.4 Emergency telephone number

Emergency information service This number is only available during the following office hours: Mon-Fri 07:30 AM - 04:15 PM

Poison centre					
Country	Name	Postal code/city	Telephone	Telefax	Opening hours
United Kingdom	National Poison Information Service		GB NHS Direct: 111 / +44 344 892 0111 (for use by Health Care Professional only)		Mon - Fri 12:00 AM - 12:00 AM

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.16	substance or mixture corrosive to metals	1	Met. Corr. 1	H290
3.2	skin corrosion/irritation	1	Skin Corr. 1	H314
3.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
4.1C	hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Cemex Truck Wash

Version number: GHS 1.0

Date of compilation: 2024-03-14

Labelling

- Signal word danger

- Pictograms

GHS05



- Hazard statements

H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P390 Absorb spillage to prevent material damage.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

hydrogen chloride, ALCOHOL C13 ISO, ETH-OXYLATED, 2-aminoethanol, ETHOXYLATED AMINES

2.3 Other hazards

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0,1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures







Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
sulphamic acid	CAS No 5329-14-6 EC No 226-218-8 Index No 016-026-00-0	10 - < 25	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Aquatic Chronic 3 / H412	
2-phenoxyethanol; phosphoric acid	CAS No 39464-70-5 EC No 609-691-9	5 - < 10	Eye Irrit. 2 / H319	

Cemex Truck Wash

Version number: GHS 1.0

Date of compilation: 2024-03-14

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
ALCOHOL C13 ISO, ETH-OXYLATED	CAS No 9043-30-5	5 - < 10	Eye Dam. 1 / H318 Aquatic Chronic 3 / H412	
hydrogen chloride	CAS No 7647-01-0 EC No 231-595-7 Index No 017-002-00-2	1 - < 5	Press. Gas C / H280 Met. Corr. 1 / H290 Acute Tox. 3 / H331 Skin Corr. 1A / H314 Eye Dam. 1 / H318 STOT SE 3 / H335	  
ETHOXYLATED AMINES	CAS No 61791-24-0 EC No 612-399-4	1 - < 5	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	  
2-aminoethanol	CAS No 141-43-5 EC No 205-483-3 Index No 603-030-00-8	1 - < 5	Acute Tox. 4 / H302 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Corr. 1B / H314 Eye Dam. 1 / H318 STOT SE 3 / H335	 

Name of substance	Specific Conc. Limits	M-Factors	ATE	Exposure route
hydrogen chloride	Met. Corr. 1; H290: C ≥ 0.1 % Eye Dam. 1; H318: C ≥ 1 %	-	>700 ppmV/4h	inhalation: gas
ETHOXYLATED AMINES	-	-	500 mg/kg	oral
2-aminoethanol	STOT SE 3; H335: C ≥ 5 %	-	1,089 mg/kg 1,100 mg/kg 11 mg/4h	oral dermal inhalation: vapour

Remarks

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

Cemex Truck Wash

Version number: GHS 1.0

Date of compilation: 2024-03-14

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Substance or mixture corrosive to metals.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂), Sulphur oxides (SO_x)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Cemex Truck Wash

Version number: GHS 1.0

Date of compilation: 2024-03-14

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation
Use local and general ventilation. Use only in well-ventilated areas.
- Handling of incompatible substances or mixtures
- Keep away from
Caustic solutions

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Corrosive conditions
Store in corrosive resistant container with a resistant inner liner.

Control of effects

Protect against external exposure, such as
frost

- Packaging compatibilities
Only packagings which are approved (e.g. acc. to ADR) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
EU	2-aminoethanol	141-43-5	IOELV	1	2.5	3	7.6			H	2006/15/EC
EU	hydrogen chloride	7647-01-0	IOELV	5	8	10	15				2000/39/EC
GB	2-aminoethanol	141-43-5	WEL	1	2.5	3	7.6				EH40/2005
GB	hydrogen chloride	7647-01-0	WEL	1	2	5	8			ga	EH40/2005

Notation

Ceiling-C

ga

H

STEL

TWA

ceiling value is a limit value above which exposure should not occur

as gases and aerosols

absorbed through the skin

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Cemex Truck Wash

Version number: GHS 1.0

Date of compilation: 2024-03-14

Relevant DNELs of components						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
sulphamidic acid	5329-14-6	DNEL	70.5 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
sulphamidic acid	5329-14-6	DNEL	10 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
hydrogen chloride	7647-01-0	DNEL	8 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
hydrogen chloride	7647-01-0	DNEL	15 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
2-aminoethanol	141-43-5	DNEL	1 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-aminoethanol	141-43-5	DNEL	0.51 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
2-aminoethanol	141-43-5	DNEL	3 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
sulphamidic acid	5329-14-6	PNEC	1.8 mg/l	aquatic organisms	freshwater	short-term (single instance)
sulphamidic acid	5329-14-6	PNEC	0.18 mg/l	aquatic organisms	marine water	short-term (single instance)
sulphamidic acid	5329-14-6	PNEC	20 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
sulphamidic acid	5329-14-6	PNEC	8.36 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
sulphamidic acid	5329-14-6	PNEC	0.84 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
sulphamidic acid	5329-14-6	PNEC	5 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-aminoethanol	141-43-5	PNEC	0.07 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-aminoethanol	141-43-5	PNEC	0.007 mg/l	aquatic organisms	marine water	short-term (single instance)
2-aminoethanol	141-43-5	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-aminoethanol	141-43-5	PNEC	0.357 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2-aminoethanol	141-43-5	PNEC	0.036 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-aminoethanol	141-43-5	PNEC	1.29 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Cemex Truck Wash

Version number: GHS 1.0

Date of compilation: 2024-03-14

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Type of material

NR: natural rubber, latex, Nitrile

- Material thickness

NR: natural rubber, latex: 1 mm
nitrile: 0,11 mm

- Breakthrough times of the glove material

>480 minutes (permeation: level 6)

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	yellow
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	>100 °C
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	not determined
Flash point	>93 °C
Auto-ignition temperature	424 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant

Cemex Truck Wash

Version number: GHS 1.0

Date of compilation: 2024-03-14

pH (value)	<2 (20 °C) (acid)
Kinematic viscosity	not determined
Solubility(ies)	not determined

Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapour pressure	32 hPa at 25 °C
-----------------	-----------------

Density and/or relative density

Density	not determined
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

9.2 Other information

Information with regard to physical hazard classes	there is no additional information
--	------------------------------------

Other safety characteristics

Liquid content	83.25 %
Solid content	15 %

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". Substance or mixture corrosive to metals.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

Cemex Truck Wash

Version number: GHS 1.0

Date of compilation: 2024-03-14

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if inhaled.

Acute toxicity estimate (ATE) of components			
Name of substance	CAS No	Exposure route	ATE
hydrogen chloride	7647-01-0	inhalation: gas	>700 ppmV/4h
ETHOXYLATED AMINES	61791-24-0	oral	500 mg/kg
2-aminoethanol	141-43-5	oral	1,089 mg/kg
2-aminoethanol	141-43-5	dermal	1,100 mg/kg
2-aminoethanol	141-43-5	inhalation: vapour	11 mg/l/4h

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

There is no additional information.

Cemex Truck Wash

Version number: GHS 1.0

Date of compilation: 2024-03-14

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (chronic) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
sulphamidic acid	5329-14-6	EC50	>60 mg/l	aquatic invertebrates	21 d
2-aminoethanol	141-43-5	EC50	2.5 mg/l	aquatic invertebrates	21 d

12.2 Persistence and degradability

Degradability of components						
Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
2-phenoxyethanol; phosphoric acid	39464-70-5	oxygen depletion	5 %	28 d		ECHA
2-aminoethanol	141-43-5	DOC removal	>90 %	21 d		ECHA

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
sulphamidic acid	5329-14-6		-4.34 (pH value: <2, 20 °C)	
2-phenoxyethanol; phosphoric acid	39464-70-5		0.72 (pH value: ~7, 25 °C)	
2-aminoethanol	141-43-5	2.5	-2.3 (25 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0,1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

12.7 Other adverse effects

Data are not available.

Cemex Truck Wash

Version number: GHS 1.0

Date of compilation: 2024-03-14

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID	UN 1760
IMDG-Code	UN 1760
ICAO-TI	UN 1760

14.2 UN proper shipping name

ADR/RID	CORROSIVE LIQUID, N.O.S.
IMDG-Code	CORROSIVE LIQUID, N.O.S.
ICAO-TI	Corrosive liquid, n.o.s.
Technical name (hazardous ingredients)	sulphamidic acid, 2-aminoethanol

14.3 Transport hazard class(es)

ADR/RID	8
IMDG-Code	8
ICAO-TI	8

14.4 Packing group

ADR/RID	II
IMDG-Code	II
ICAO-TI	II

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Cemex Truck Wash

Version number: GHS 1.0

Date of compilation: 2024-03-14

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) - Additional information

Classification code C9

Danger label(s) 8



Special provisions (SP) 274

Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

Transport category (TC) 2

Tunnel restriction code (TRC) E

Hazard identification No 80

Emergency Action Code 2X

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID) - Additional information

Classification code C9

Danger label(s) 8



Special provisions (SP) 274

Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

Transport category (TC) 2

Hazard identification No 80

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant -

Danger label(s) 8



Special provisions (SP) 274

Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

EmS F-A, S-B

Stowage category B

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 8



Special provisions (SP) A3

Excepted quantities (EQ) E2

Cemex Truck Wash

Version number: GHS 1.0

Date of compilation: 2024-03-14

Limited quantities (LQ)

0,5 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Deco-Paint Directive

VOC content	7 %
-------------	-----

Industrial Emissions Directive (IED)

VOC content	7 %
-------------	-----

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

Water Framework Directive (WFD)

none of the ingredients are listed

Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

National regulations (GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list

none of the ingredients are listed

Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)			
Name of substance	Name acc. to inventory	CAS No	No
Cemex Truck Wash	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		3

National inventories

Country	Inventory	Status
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)

Legend

REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

Cemex Truck Wash

Version number: GHS 1.0

Date of compilation: 2024-03-14

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
Acute Tox.	Acute toxicity
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air

Cemex Truck Wash

Version number: GHS 1.0

Date of compilation: 2024-03-14

Abbr.	Descriptions of used abbreviations
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
log KOW	n-Octanol/water
Met. Corr.	Substance or mixture corrosive to metals
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Press. Gas	Gas under pressure
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H280	Contains gas under pressure; may explode if heated.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.

Cemex Truck Wash

Version number: GHS 1.0

Date of compilation: 2024-03-14

Code	Text
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.