

# ENVIRONMENTAL PRODUCT DECLARATION RUGBY CEMENT PLANT CEM II/A-L 52,5 N

EPD®  
THE INTERNATIONAL EPD® SYSTEM

ECO PLATFORM  
EPD  
VERIFIED

In accordance with ISO 14025:2006 and  
EN 15804:2012+A2:2019/AC:2021 for:  
**Rugby Cement Plant CEM II/A-L 52,5 N**

from  
**Cemex UK Ltd**

<b>Programme</b>	The International EPD® System, <a href="http://www.environdec.com">www.environdec.com</a>
<b>Programme operator</b>	EPD International AB
<b>EPD registration number</b>	EPD-IES-0014484
<b>Publication date</b>	2024-06-17
<b>Valid until</b>	2029-06-17

An EPD should provide current information and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at [www.environdec.com](http://www.environdec.com)

 CEMEX

# GENERAL INFORMATION

## ACCOUNTABILITIES FOR PCR, LCA AND INDEPENDENT, THIRD-PARTY VERIFICATION

### Product Category Rules (PCR)

CEN standard EN 15804 serves as the Core Product Category Rules (PCR)

Product Category Rules (PCR):

- PCR 2019:14 Construction products; Version 1.3.4
- c-PCR-001 Cement and Building Lime (EN 16908:2017+A1:2022) 2022-05-18
- UN CPC: 3744

PCR review was conducted by: The Technical Committee of the International EPD System

### Life Cycle Assessment (LCA)

#### LCA Accountability

Paul Fletcher

CEMEX House, Binley Business Park, Harry Weston Road, Coventry CV3 2TY. United Kingdom  
pauldavid.fletcher@cemex.com

### Third-party verification

- Independent third-party verification of the declaration and data, according to ISO 14025:2006, via:  
EPD verification by individual verifier
- Third-party verifier: Angela Schindler, Umweltberatung
- Approved by: The International EPD® System

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but registered in different EPD programmes, or not compliant with EN 15804, may not be comparable. For two EPDs to be comparable, they must be based on the same PCR (including the same version number) or be based on fully-aligned PCRs or versions of PCRs; cover products with identical functions, technical performances and use (e.g. identical declared/functional units); have equivalent system boundaries and descriptions of data; apply equivalent data quality requirements, methods of data collection, and allocation methods; apply identical cut-off rules and impact assessment methods (including the same version of characterisation factors); have equivalent content declarations; and be valid at the time of comparison. For further information about comparability, see EN 15804 and ISO 14025.



The International EPD® System



EPD International AB  
Box 210 60  
SE-100 31 Stockholm  
Sweden



[www.environdec.com](http://www.environdec.com)



[info@environdec.com](mailto:info@environdec.com)

# CONTENTS

## COMPANY INFORMATION

4

Owner of the EPD	4
Description of the organisation	4
Product-related or management system-related certifications	4
Name and location of production site(s)	4

## PRODUCT INFORMATION

5

Product name	5
Product identification	5
Product description	5
Materials composition	5
Technical specifications and physical properties of the product	5
Geographical scope	5

## LCA INFORMATION

6

Functional unit/declared unit	6
Reference service life	6
Time representativeness	6
Database(s) and LCA software used	6
Description of system boundaries	6
Data collection	7
Power mix	7
CO <sub>2</sub> -Certificates	8
Cut-off rules	8
Allocations	8

## RESULTS OF THE ENVIRONMENTAL PERFORMANCE INDICATORS

## DIFFERENCES VERSUS PREVIOUS VERSIONS

## REFERENCES

## CONTACT INFORMATION

# COMPANY INFORMATION

## Owner of the EPD

 **Cemex UK Ltd**

 **Cemex House,  
Binley Business Park,  
Harry Weston Road,  
Coventry  
CV3 2TY  
United Kingdom**

 **[www.cemex.co.uk](http://www.cemex.co.uk)**

## DESCRIPTION OF THE ORGANISATION


Cemex UK is a leading supplier of cement, ready mix concrete, mortars, screeds, aggregates, asphalts, concrete block paving and concrete blocks.

## PRODUCT-RELATED OR MANAGEMENT SYSTEM-RELATED CERTIFICATIONS

Cemex UK cement plants have management systems certified according to ISO 9001:2015 "Quality Management", ISO 14001:2015 "Environmental Management" standards and ISO 50001:2018 "Energy Management". Additionally, the organization's greenhouse gas emissions are verified in accordance with Commission Regulation (EU) No. 2018/2067 on the verification of data and the accreditation of verifiers pursuant to Directive 2003/87/EC. The calculation of the Product Footprint for all Cements is carried out in compliance with EN 15804:2022.

## NAME AND LOCATION OF PRODUCTION SITE(S)

Rugby Cement Plant, Rugby.



# PRODUCT INFORMATION

## PRODUCT NAME

CEM II/A-L 52,5N

## PRODUCT IDENTIFICATION

Certificate of Conformity no: 1333-CPR-00256

## PRODUCT DESCRIPTION

CEM II/A-L 52,5N (Cemstone) is a factory produced Portland composite cement with the addition of limestone, containing 80-94% clinker. It is produced in accordance with the EN 197-1 standard. Cemstone provides benefits in a wide range of concrete, mortar, render, screed and grout applications being suitable for use as an alternative to Portland cement in most types of concrete.

It is recommended to produce concrete with requirements for high initial and final mechanical resistance, and injection concrete. It is suitable to produce precast and prefabricated elements, as well as prestressed constructions for the construction of public and commercial buildings.

It is particularly recommended for use in concrete work at low temperatures, for the construction of structures where quick formwork removal, handling of elements, or early structural loading is required. Additionally, it is suitable to produce waterproof concrete and frost resistant concrete.

## MATERIALS COMPOSITION

### Product raw material

Product components	Weight-%	Post-consumer material, weight-%	Biogenic material, weight-% and kg C/kg
Clinker	80-94	0	0
Limestone	6-20	0	0
Other constituents	0-5	0	0
TOTAL	100	0	0

\*Gypsum is not included in the aforementioned composition

### Packaging material

This cement is being shipped in bulk.

### Dangerous substances from the candidate list of SVHC for Authorisation

Declared products contain less than 0,1% or no hazardous substance, from the "Candidate list of Substances of Very High Concern", updated 14/06/2023.

Cement is a preparation and is therefore not subject to REACH registration, although it must also be classified and labelled. Under the European Union (Withdrawal) Act 2018, the EU REACH Regulation was brought into UK law on 1 January 2021 and is known as UK REACH.

REACH, and related legislation, were replicated in the UK with the changes needed to make it operable in a domestic context. The key principles of the EU REACH Regulation were retained in UK REACH.

## TECHNICAL SPECIFICATIONS AND PHYSICAL PROPERTIES OF THE PRODUCT




Product sheet for the cement can be retrieved [here](#).



Further information can be found at [www.cemex.co.uk](http://www.cemex.co.uk)

## GEOGRAPHICAL SCOPE

Geographical scope of the product is Europe. The product is produced in the United Kingdom.



# LCA INFORMATION

---

## FUNCTIONAL UNIT / DECLARED UNIT

A declared unit is 1 tonne of cement.

## REFERENCE SERVICE LIFE

Not relevant due to the “cradle to gate” boundary conditions.

## TIME REPRESENTATIVENESS

The foreground production data correspond to the period from January 1, 2022 to December 31, 2022.

## DATABASE(S) AND LCA SOFTWARE USED

GCCA Industry EPD Tool for Cement and Concrete (v.4.2), International version and Ecoinvent database (v.3.5).





### DESCRIPTION OF SYSTEM BOUNDARIES

The scope of the study is “Cradle to Gate”, covering the product stage - modules A1-A3:

#### A1 - Raw Materials Supply

This module takes into account raw material extraction, processing and energy used in the production process.

#### A2 - Transport

This module includes transportation of the raw materials and fuels from supplier to plant gate. Transportation types are considered as sea, road and conveyor belts.

#### A3 - Manufacturing

This stage includes energy and water consumption during the manufacturing process, as well as the processing of any waste arising from this stage. Followed production processes are:

- Quarry Operations
- Crusher
- Raw Mill & Coal Mill
- Rotary Kiln
- Cement Mill
- Bulk loading

### System diagram

	Product stage			Construction process stage		Use stage							End of life stage				Resource recovery stage
	Raw material supply	Transport	Manufacturing	Transport	Construction installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
<b>Module</b>	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
<b>Modules declared</b>	X	X	X	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
<b>Geography</b>	UK	UK	UK	-	-	-	-	-	-	-	-	-	-	-	-	-	-
<b>Specific data used</b>	>99%			-	-	-	-	-	-	-	-	-	-	-	-	-	-
<b>Variation - products</b>	Not relevant			-	-	-	-	-	-	-	-	-	-	-	-	-	-
<b>Variation - sites</b>	Not relevant			-	-	-	-	-	-	-	-	-	-	-	-	-	-

X= included, ND = module not declared; EUR = Europe, UK = United Kingdom





## CO<sub>2</sub>-CERTIFICATES

No compensation offsets have been used in the LCA calculation.

## CUT-OFF RULES

All raw materials and energy input to the manufacturing process have been included.

Process energy, water use and discharge and process and general waste are included.

In accordance with EN 15804, emissions from capital goods (production and transportation of machinery, equipment, and buildings), employee transportation, and maintenance materials are not included.

## ALLOCATIONS

The total values for fuel consumed by the operation of vehicles for transportation within the plant, quantities of water withdrawn and discharged, and the amounts of waste generated, over a one-year period, are allocated to clinker.

## Secondary materials, co-product allocations

The only co-products used are small quantities of paper ash and slag in clinker.

In accordance with the GCCA Manual zero allocation has been applied as we receive a payment for the materials.



# RESULTS OF THE ENVIRONMENTAL PERFORMANCE INDICATORS

The estimated impact results are only relative statements, which do not indicate the endpoints of the impact categories, exceeding threshold values, safety margins and/or risks.

## MANDATORY IMPACT CATEGORY INDICATORS ACCORDING TO EN 15804

Results per declared unit of 1000 kg of CEM I 52.5 N cement		
Indicator	Unit	A1-A3
<b>GWP- fossil<sup>1</sup></b>	kg CO <sub>2</sub> eq.	712
<b>GWP- biogenic<sup>1</sup></b>	kg CO <sub>2</sub> eq.	0.68
<b>GWP-luluc</b>	kg CO <sub>2</sub> eq.	0.0373
<b>GWP-total<sup>1</sup></b>	kg CO <sub>2</sub> eq.	713
<b>ODP</b>	kg CFC 11 eq.	5.97E-6
<b>AP</b>	mol H+ eq.	1.24
<b>EP-freshwater</b>	kg P eq.	4.48E-2
<b>EP-marine</b>	kg N eq.	2.88E-3
<b>EP-terrestrial</b>	mol N eq.	5.94
<b>POCP</b>	kg NMVOC eq.	1.49
<b>ADP-minerals&amp;metals*</b>	kg Sb eq.	1.73E-4
<b>ADP-fossil*</b>	MJ	1346
<b>WDP*</b>	m <sup>3</sup>	11.55

<sup>1</sup>The indicated values (gross values) include the greenhouse gas emissions from the incineration of secondary fuels at clinker production. The net GWP-tot (excluding the emissions from the incineration of secondary fuels at clinker production) is 6.53E2 kg CO<sub>2</sub>-eq. The net GWP-fos is 6.53E2 kg CO<sub>2</sub>-eq. The net GWP-bio is 4.31E-1 kg CO<sub>2</sub>-eq. The indicated values (gross values) include the greenhouse gas emissions from the incineration of secondary fuels at clinker production. The net GWP-GHG (excluding the emissions from the incineration of secondary fuels at clinker production) is 6.53E2 kg CO<sub>2</sub>-e

\*Disclaimer: The results of this environmental impact indicator shall be used with care as the uncertainties of these results are high or as there is limited experience with the indicator.



## ACRONYMS

GWP-fossil	Global Warming Potential fossil fuels
GWP-biogenic	Global Warming Potential biogenic
GWP-luluc	Global Warming Potential land use and land use change
ODP	Depletion potential of the stratospheric ozone layer
AP	Acidification potential, Accumulated Exceedance
EP-freshwater	Eutrophication potential, fraction of nutrients reaching freshwater end compartment
EP-marine	Eutrophication potential, fraction of nutrients reaching marine end compartment
EP-terrestrial	Eutrophication potential, Accumulated Exceedance
POCP	Formation potential of tropospheric ozone
ADP-minerals&metals	Abiotic depletion potential for non-fossil resources
ADP-fossil	Abiotic depletion for fossil resources potential
WDP	Water (user) deprivation potential, deprivation-weighted water consumption



### ADDITIONAL MANDATORY AND VOLUNTARY IMPACT CATEGORY INDICATORS

Results per declared unit of 1000 kg of CEM I 52.5 N cement					
Indicator	Unit	A1	A2	A3	A1-A3 (Total)
<b>GWP-GHG<sup>2</sup></b>	kg CO <sub>2</sub> eq.	708	1.61	2.74	713

<sup>2</sup>The indicated values (gross values) include the greenhouse gas emissions from the incineration of secondary fuels at clinker production. The net GWP-tot (excluding the emissions from the incineration of secondary fuels at clinker production) is 6.53E2 kg CO<sub>2</sub>-eq. The net GWP-fos is 6.53E2 kg CO<sub>2</sub>-eq

### RESOURCE USE INDICATORS

Results per declared unit of 1000 kg of CEM I 52.5 N cement			
Indicator	Unit	A1-A3	
<b>PERE</b>	MJ	553	
<b>PERM</b>	MJ	0	
<b>PERT</b>	MJ	553	
<b>PENRE</b>	MJ	1346	
<b>PENRM</b>	MJ	0	
<b>PENRT</b>	MJ	1346	
<b>SM</b>	kg	21.2	
<b>RSF</b>	MJ	1312	
<b>NRSF</b>	MJ	512	
<b>NFW</b>	m <sup>3</sup>	0.306	

### WASTE INDICATORS<sup>3</sup>

Results per declared unit of 1000 kg of CEM I 52.5 N cement		
Indicator	Unit	A1-A3
<b>Hazardous waste disposed</b>	kg	0.16
<b>Non-hazardous waste disposed</b>	kg	0
<b>Radioactive waste disposed</b>	kg	0

<sup>3</sup>The waste indicators in the Global Cement and Concrete Association (GCCA) tool exclusively pertain to the foreground system, diverging from the requirements outlined in EN 15804+A2, which mandates consideration of the entire life cycle. Consequently, this deviation from the standard results in an inherent incomparability with other Environmental Product Declarations (EPDs) with regards to waste indicators.

### ACRONYMS

<b>PERE</b>	Use of renewable primary energy excluding renewable primary energy resources used as raw materials
<b>PERM</b>	Use of renewable primary energy resources used as raw materials
<b>PERT</b>	Total use of renewable primary energy resources
<b>PENRE</b>	Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials
<b>PENRM</b>	Use of non-renewable primary energy resources used as raw materials
<b>PENRT</b>	Total use of non-renewable primary energy re-sources
<b>SM</b>	Use of secondary material
<b>RSF</b>	Use of renewable secondary fuels
<b>NRSF</b>	Use of non-renewable secondary fuels
<b>NFW</b>	Use of net fresh water



## OUTPUT FLOW INDICATORS

Results per declared unit of 1000 kg of CEM I 52.5 N cement		
Indicator	Unit	A1-A3
Components for re-use	kg	0
Material for recycling	kg	1.25
Materials for energy recovery	kg	0
Exported energy, electricity	MJ	0
Exported energy, thermal	MJ	0

## OTHER ENVIRONMENTAL PERFORMANCE INDICATORS

Results per declared unit of 1000 kg of CEM I 52.5 N cement		
Indicator	Unit	A1-A3
Potential incidence of disease due to PM emissions	Disease incidence	1.05E-5
Potential human exposure efficiency relative to U235	kBq U235 eq.	1.789
Potential Comparative Toxic Unit for ecosystems	CTUe	54.9
Potential Comparative Toxic Unit for humans - cancer	CTUh	1.75E-6
Potential Comparative Toxic Unit for humans - non-cancer	CTUh	7.10E-5
Potential soil quality index	Dimensionless	5687

# DIFFERENCES VERSUS PREVIOUS VERSIONS

---

First EPD version - no previous versions



# REFERENCES

The following reference documents have been used as the basis for this methodology, For dated references, only the edition cited applies, For undated references, the latest edition of the referenced document (including any amendments) applies:

- Cement Standards: EN 197-1
- EN 15804:2012+A2:2019, Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products
- EPD General Programme Instructions for the International EPD System, Version 4,0, Date 2021-03-29
- EPD Product Category Rules (PCR), Data 2022-11-01, Construction products, PCR 2019:14, Version 1.3.4
- EPD Cement and Building Lime (EN16908:2017+A1:2022), Product group classification: UN CPC 374, C-PCR-001 (PCR 2019:14), Version: 2022-05-18
- EPD PCR 2019:14 Construction products, version 1,0 (EN 15804+A2)
- EN ISO 14025:2010, Environmental labels and declarations - Type III environmental declarations - Principles and procedures (ISO 14025:2006)
- EN ISO 14040:2008/A1, Environmental management - Life cycle assessment - Principles and framework (ISO 14040:2006/ Amd 1:2020; EN ISO 14040:2006/A1:2020)
- EN ISO 14044:2006, Environmental management - Life cycle assessment - Requirements and guidelines (ISO 14044:2006)
- EN ISO 14067:2018, Greenhouse gases - Carbon footprint of products - Requirements and guidelines for quantification (ISO 14067:2018)
- ISO 15686-1, Buildings and constructed assets - Service life planning - Part 1: General principles and framework
- ISO 15686-2, Buildings and constructed assets - Service life planning - Part 2: Service life prediction procedures
- ISO 15686-7, Buildings and constructed assets - Service life planning - Part 7: Performance evaluation for feedback of service life data from practice
- ISO 15686-8:2008, Buildings and constructed assets - Service life planning - Part 8: Reference service life and service life estimation
- ISO 21930:2017, Sustainability in building construction and civil engineering - Core rules for environmental product declarations of construction products and services
- European Commission - Joint Research Centre - Institute for Environment and Sustainability: International Reference Life Cycle Data System (ILCD) Handbook - Nomenclature and Conventions, 2010, EUR 24384 EN, Luxembourg, Publications Office of the European Union; 2010, ISBN 978-92-79-15861-2
- Industry EPD Tool for Cement and Concrete (<https://concrete-epd-tool.org/>)
  - User Guide (v4.2, International version, 18 December 2023)
  - LCA Model (v4.2, International version, 18 December 2023)
  - LCA Database (v4.2, 18 December 2023)



# CONTACT INFORMATION

## Owner of Declaration

 **Cemex UK Cement Ltd**

 **Cemex House,  
Binley Business Park,  
Harry Weston Road,  
Coventry  
CV3 2TY  
United Kingdom**

 **[www.cemex.co.uk](http://www.cemex.co.uk)**

## LCA Author

 **Cemex UK Cement Ltd**

 **Cemex House,  
Binley Business Park,  
Harry Weston Road,  
Coventry  
CV3 2TY  
United Kingdom**

 **[www.cemex.co.uk](http://www.cemex.co.uk)**

 **[pauldavid.fletcher@cemex.com](mailto:pauldavid.fletcher@cemex.com)**

## Third party verifier

 **Angela Schindler Umweltberatung**

 **Tüfinger Str. 12  
88682 Salem, Germany**

 **[www.schindler-umwelt.de](http://www.schindler-umwelt.de)**

 **[angela@schindler-umwelt.de](mailto:angela@schindler-umwelt.de)**

 **EPD®**  
THE INTERNATIONAL EPD® SYSTEM







 **EPD**®  
THE INTERNATIONAL EPD® SYSTEM



